

BERENDS STICK RAKES

- Underframe clearance of 400mm
- Adjustable 32 x 10mm 'S' tines mounted at 6" spacings
- Tines are fitted with replaceable points (grass points available for pasture harrowing)
- Toolbar constructed from 2" square K1045 (high tensile) solid bar
- Available as standard on toolbar linkage and can be made offset for getting closer to trees, fences and sheds. Supported by quick release clamp and wedge arrangement
- Optional model can be made to fit to existing Berends Standard and Medium Grader Blades. (NB Top and bottom halves are priced separately on this model)



- 0345** Berends Stick Rake 6' (13 tines)
c/w toolbar linkage
- 0342** Berends Stick Rake 7'6" (15 tines)
c/w toolbar linkage
- 0343** Berends Stick Rake 9' (19 tines)
c/w toolbar linkage
- 0344** Berends Stick Rake 10'6" (21 tines)
c/w toolbar linkage

BERENDS DEEP TILLAGE PLOUGH

- Heavy duty 100 x 100 x 9mm tine mounting frame
- High tensile cast shank assembly with 24" (610mm) underframe clearance with 1" shear pin protection. Replaceable points and shin guards - also available with tungsten tips.
- Breakforce approximately 4000 ft.lbs.
- Tine spacing set at 12" (300mm)
- Approximately 15HP required per tine
- Fitted standard with adjustable pair of Holden wheels for depth control
- Optional coulters available to reduce surface disturbance in pasture
- Optional hydraulic crumbler rollers also available to help create a level surface and reduce crusting in the surface



- 0320** Berends Deep Tillage Plough 5 Tine
- 0322** Berends Deep Tillage Plough 7 Tine
- 0324** Berends Deep Tillage Plough 9 Tine
- 0326** Berends Deep Tillage Plough 11 Tine

STUMP JUMP CHISEL PLOUGHS

BERENDS STUMP JUMP CHISEL PLOUGHS

- Ideal for primary cultivation, pasture renovation and weed control etc.
- Heavy duty 50x25mm silicone chrome spring steel tines fitted with a 350x75mm adjustable coil spring
- Heavy duty frame made from 76x76x6.3mm hollow section
- Under frame clearance of 520mm
- Standard 400x65x12mm reversible chisel points



CODE	TINES	CUT		WEIGHT
0192	5	5'	1.5m	230kg
0194	7	7'	2.1m	310kg
0196	9	9'	2.7m	390kg
0198	11	11'	3.3m	490kg
0200	Depth Wheel Kit			

JARRETT STUMP JUMP CHISEL PLOUGHS

- Designed for primary tillage
- 50x25mm spring steel chisel tines with strong fabricated tine clamps
- Frame made from 65mm (2½") solid steel toolbar
- Reversible chisel points



CODE	MODEL	TINES	CUT		WEIGHT
CP150	CP150	5	5'	1.5m	310kg
CP210	CP210	7	7'	2.1m	400kg
CP270	CP270	9	9'	2.7m	490kg
CP330	CP330	11	11'	3.3m	590kg
25200	Depth Wheel Kit				