

BERENDS S-TINE CULTIVATORS

STANDARD MODEL

- Multi purpose implement for breaking up and renovating pastures, preparing seedbeds and cultivating etc.
- 100mm tine spacing with working centres fitted on 4 bars giving a 300mm clearance between tines
- Tines can be moved along the frame for row crop work
- Headstock can be offset for working under vines and trees etc.



CODE	TINE	CUT	WEIGHT	OPTIONAL CRUMBLERS	
				CODE	WEIGHT
0311	12	1.2m	118kg	0235	75kg
0312	16	1.6m	154kg	0236	85kg
0313	20	2.0m	172kg	0237	95kg
0314	24	2.4m	199kg	0238	100kg
0315	28	2.8m	206kg	0239	120kg
0316	32	3.2m	233kg	0240	130kg
0317	36	3.6m	260kg	0241	140kg
0220	Wheel kit to suit 12-28 tine models				
0230	Wheel kit to suit 32-36 tine models				

FARM-AID STICK RAKES

- 3pt linkage
- 70x50 RHS main frame
- Anti-kick bar fitted for greater strength and minimised tine breakage
- ¾" spring steel round curved tines
- Tines spaced 6" apart - other spacings available



FA199	FA200	FA201	FA202	FA203	FA204
3'	4'	6'	8'	10'	12'

BERENDS STICK RAKES

- Underframe clearance of 400mm
- Adjustable 32 x 10mm 'S' tines mounted at 6" spacings
- Tines are fitted with replaceable points (grass points available for pasture harrowing)
- Toolbar constructed from 2" square K1045 (high tensile) solid bar
- Available as standard on toolbar linkage and can be made offset for getting closer to trees, fences and sheds. Supported by quick release clamp and wedge arrangement
- Optional model can be made to fit to existing Berends Standard and Medium Grader Blades. (NB Top and bottom halves are priced separately on this model)



- 0345** Berends Stick Rake 6' (13 tines)
c/w toolbar linkage
- 0342** Berends Stick Rake 7'6" (15 tines)
c/w toolbar linkage
- 0343** Berends Stick Rake 9' (19 tines)
c/w toolbar linkage
- 0344** Berends Stick Rake 10'6" (21 tines)
c/w toolbar linkage

BERENDS DEEP TILLAGE PLOUGH

- Heavy duty 100 x 100 x 9mm tine mounting frame
- High tensile cast shank assembly with 24" (610mm) underframe clearance with 1" shear pin protection. Replaceable points and shin guards - also available with tungsten tips.
- Breakforce approximately 4000 ft.lbs.
- Tine spacing set at 12" (300mm)
- Approximately 15HP required per tine
- Fitted standard with adjustable pair of Holden wheels for depth control
- Optional coulters available to reduce surface disturbance in pasture
- Optional hydraulic crumbler rollers also available to help create a level surface and reduce crusting in the surface



- 0320** Berends Deep Tillage Plough 5 Tine
- 0322** Berends Deep Tillage Plough 7 Tine
- 0324** Berends Deep Tillage Plough 9 Tine
- 0326** Berends Deep Tillage Plough 11 Tine